

LISTING OF THE CLAIMS

The following listing of claims replaces all prior versions.

1 (CURRENTLY AMENDED). A current-voltage transforming circuit comprising:

a photo detector generating a photo current in response to a photo signal inputted into the photo detector;

an amplifier amplifying the photo current received from the photo detector;

an emitter follower coupled to the amplifier;

an output buffer coupled to the emitter;

a current detecting limiter unit having an input terminal and an output terminal to output a limiter current when an output current of the amplifier is greater than a predetermined reference value; and

a feedback resistor coupled between the input of said amplifier and the output of [of] said output buffer;

wherein the input terminal of the current detecting limiter unit is coupled to a junction between the emitter follower and the output buffer.

CANCEL 2 - 3

4 (ORIGINAL). The circuit of claim 1, wherein the output terminal of the current detecting limiter unit is coupled to an input of the amplifier.

5 (ORIGINAL). The circuit of claim 1, wherein the output terminal of the current detecting limiter unit is coupled to ground.

6 (CURRENTLY AMENDED). [The circuit of claim 1, wherein the amplifier comprises:]

A current-voltage transforming circuit comprising:

a photo detector generating a photo current in response to a photo signal inputted into the photo detector;

an amplifier amplifying the photo current received from the photo detector;

an emitter follower coupled to the amplifier;

an output buffer coupled to the emitter;

a current detecting limiter unit having an input terminal and an output terminal to output a limiter current when an output current of the amplifier is greater than a

predetermined reference value;

a feedback resistor coupled between the input of said amplifier and the output of said output buffer; and

a differential amplifier receiving an input voltage of the photo current generated from the photo detector and a reference voltage.

7 (ORIGINAL). The circuit of claim 6, wherein the differential amplifier comprises a pair of differential transistors and first and second biases supplied to the differential transistors.

8 (CURRENTLY AMENDED). [The circuit of claim 1, wherein the current detecting limiter unit comprises:]

A current-voltage transforming circuit comprising:

a photo detector generating a photo current in response to a photo signal inputted into the photo detector;

an amplifier amplifying the photo current received from the photo detector;

an emitter follower coupled to the amplifier;

an output buffer coupled to the emitter;

a current detecting limiter unit having an input terminal and an output terminal to output a limiter current when an output current of the amplifier is greater than a predetermined reference value;and

a feedback resistor coupled between the input of said amplifier and the output of said output buffer;

wherein said current limiter unit includes

a voltage source;

first and second resistors;

a first transistor having collector coupled to the voltage source, a base receiving the output current, and an emitter coupled to the first and second resistors; and

a second transistor having a collector coupled to receive a current from one of the emitter follower and the output buffer, an emitter coupled to output the limiter current, and a base coupled to a junction between the first and second resistors.

9 (ORIGINAL). The circuit of claim 8, wherein the first and second transistors comprise:

an NPN type transistor.

10 (ORIGINAL). The circuit of claim 8, wherein the second transistor is turned on

when $V_{b2} > V_{REF} + V_{beq2}$ where V_{b2} is a voltage of the junction, V_{REF} is a reference voltage, and V_{beq2} is a base and emitter voltage of the second transistor.

11. CANCEL

12 (PRESENTLY AMENDED). [The circuit of claim 11,] A current-voltage transforming circuit comprising:

a photo detector generating a photo current in response to a photo signal inputted into the photo detector;

an amplifier amplifying the photo current received from the photo detector;

an emitter follower coupled to the amplifier;

an output buffer coupled to the emitter;

a current detecting limiter unit having an input terminal and an output terminal to output a limiter current when an output current of the amplifier is greater than a predetermined reference value;and

a feedback resistor coupled between the input of said amplifier and the output of said output buffer;

wherein the output terminal of the current detecting limiter unit includes:

first and second sub-output terminals coupled to the amplifier and ground,
respectively; and

wherein the current detecting limiter unit comprises:

a voltage source;

first and second resistors;

a first transistor having collector coupled to the voltage source, a base receiving the output current, and an emitter coupled to the first and second resistors; and.

a second transistor having a collector coupled to receive a current from one of the emitter follower and the output buffer, an emitter coupled to the first sub-output terminal, and a base coupled to a junction between the first and second resistors.

13 (CURRENTLY AMENDED). The circuit of claim [11] 12, wherein the current detecting limiter unit further comprises:

[a voltage source;

first and second resistors;

a first transistor having collector coupled to the voltage source, a base receiving the output current, and an emitter coupled to the first and second resistors;

a second transistor having a collector coupled to receive a current from one of the emitter follower and the output buffer, an emitter coupled to the first sub-output terminal, and a base coupled to a junction between the first and second resistors; and]

a third transistor having a collector coupled to receive the current from one of the emitter follower and the output buffer, an emitter coupled to the second sub-output terminal, and a base coupled to a junction between the first and second resistors.

14 (CURRENTLY AMENDED) The circuit of claim [11] 12 wherein the second resistor comprises:

a variable resistor.

15 (CURRENTLY AMENDED). [The circuit of claim 1,] A current-voltage transforming circuit comprising:

a photo detector generating a photo current in response to a photo signal inputted into the photo detector;

an amplifier amplifying the photo current received from the photo detector;

an emitter follower coupled to the amplifier;

an output buffer coupled to the emitter;

a current detecting limiter unit having an input terminal and an output terminal to output a limiter current when an output current of the amplifier is greater than a predetermined reference value; and

a feedback resistor coupled between the input of said amplifier and the output of said output buffer;

wherein the current detecting limiter unit [comprises] includes :

a voltage source;

first and second resistors;

a first transistor having collector coupled to the voltage source and the first resistor, an emitter coupled to ground and the second resistor, and a base coupled to receive the photo current; and

a second transistor having an emitter to receive a current from one of the emitter follower and the output buffer, a collector coupled to output the limiter current, and a base coupled to a junction between the first resistor and the first transistor.

16 (ORIGINAL). The circuit of claim 15, wherein the first transistor comprises an NPN type transistor, and the second transistor comprises a PNP type transistor.

17 (ORIGINAL). The circuit of claim 15, wherein the current detecting limiter unit comprises:

a third transistor having a base connected to the collector of the second transistor, a collector connected to the emitter of the second transistor, and an emitter coupled to output the limiter current.

18 (ORIGINAL). The circuit of claim 17, wherein the third transistor comprises an NPN type transistor.

19 - 30 CANCELLED.